



1071-CPD

Platon Multi
(Mass per unit area = 450 g/m²)

Isola as, Platon Factory, Lienfossveien 5, N-3678 Notodden, Norway.

08

CPD certificate no.
1071-CPD-1196
1197

EN 13967:2004 / EN 13984:2004

Product type
Damp proof ventilating and drainage sheet / Ventilating and draining
vapour control layer

Characteristic

Reaction to fire:	F
Tensile properties:	
Longitudinal strength (min.):	290 N/50 mm
Transverse strength (min.):	260 N/50 mm
Resistance to static loading, $\phi_{tool}= 10\text{mm}$:	Pass at 20 kg
Resistance to impact, $w_{tool}= 500\text{g}$:	Pass at 0.50 m
Resistance to tearing (min.):	Greater than 330 N
Joint Strength (min.):	55 N
Watertightness:	Pass at 2 kPa
Durability:	
After heat ageing:	Pass
Against chemicals:	Pass
Water Vapour resistance:	260 m \pm 25%
Durability:	
After heat ageing:	Pass
Durability against alkali:	Pass
Dangerous substances:	None
Resistance to deformation under load (max.):	6% at kN 50/m ²

For Isola as, Platon Factory

Richard I. Waterhouse,
Teamleader, PTS.