



## Product Search by NBS Clause

Product	Summary text	Referenced in clauses...
Platon DE25	A drainage and water storage layer for use in green roof applications.	Q37 (Green Roofs) 350
Platon Double Drain	An impermeable polyethylene studded sheet with a polypropylene filter fabric bonded to the top surface of the studs.	J40 (Flexible sheet tanking, damp proofing) 70, 295, 380; R16 (Ground water pressure relief drainage) 380
Platon Multi	An impermeable high density polyethylene (HDPE) studded membrane for use as an internal liner.	J40 (Flexible sheet tanking, damp proofing) 290
Platon P20	A heavy duty high density polyethylene (HDPE) deep studded cavity drain membrane principally used on floors.	J40 (Flexible sheet tanking, damp proofing) 290
Platon P5	A high density polyethylene (HDPE) studded cavity drain membrane for internal use for both walls and floors.	J40 (Flexible sheet tanking, damp proofing) 290
Platon Plaster Base	An impermeable high density polyethylene (HDPE) studded wall/ ceiling membrane for direct plastering.	J40 (Flexible sheet tanking, damp proofing) 290
Radon Stop 400	A radon and damp proof membrane for floors and foundations.	J40 (Flexible sheet tanking, damp proofing) 35, 140
SBR Latex Admixture	An SBR latex admixture for cementitious mixes.	M20 (Plastered/Rendered/ Roughcast coatings) 62, 449
Tribor 10	Boron based insecticidal and fungicidal wood and masonry preservative.	C52 (Fungus/beetle eradication) 47, 62, 323, 343
Tribor 20	Boron based insecticidal and fungicidal wood preservative.	C52 (Fungus/beetle eradication) 47, 323
Tribor Gel	Boron based, fungicidal, gel wood preservative.	C52 (Fungus/beetle eradication) 47, 323
Tribor Plus	Boron based gel for the eradication of death watch beetle.	C52 (Fungus/beetle eradication) 47, 323
Triject 2	Organic solvent based dpc liquid, designed for injection into walls affected by rising damp.	C45 (Damp proof course renewal/insertion) 30, 220
Triject 3	Water-based dpc liquid, designed for injection into walls affected by rising damp.	C45 (Damp proof course renewal/insertion) 30, 220
Trimethrim OS	Organic solvent, insecticidal wood preservative.	C52 (Fungus/beetle eradication) 47, 323
Trimix 1	A water and salt resistant additive for sand/cement mortars.	M20 (Plastered/Rendered/ Roughcast coatings) 62, 449
Trimol 40 Water Based Epoxy Coating	A two-component water based epoxy coating for floors and walls.	J30 (Liquid applied damp proofing) 10, 130
Trimol 41 Cement Reinforced Epoxy Coating	A three component cement reinforced epoxy coating for walls, floors and soffits.	J30 (Liquid applied damp proofing) 10, 130
Tripaste	Insecticidal and fungicidal wood preservative in paste form.	C52 (Fungus/beetle eradication) 47, 323
Triproof 2 Water Repellent	Suitable for external use on stone, brickwork and render.	J30 (Liquid applied damp proofing) 10, 130, M60, 18, 170
Triproof 290 Water Repellent	Water repellent, suitable for application on newly rendered or re-pointed brickwork.	J30 (Liquid applied damp proofing) 10, 130, M60, 18, 170
Triproof AQ Water Repellent	For use as a water repellent over masonry, brickwork, concrete and renders.	J30 (Liquid applied damp proofing) 10, 130, M60, 18, 170



## Product Search by NBS Clause

Product	Summary text	Referenced in clauses...
Tri-Rend	A salt inhibiting and plasticizing additive for sand/ cement mortars and renders.	M20 (Plastered/Rendered/Roughcast coatings) 62, 449
Tri-Seal Epoxy Resin Coating	A two-part epoxy resin coating, typically used as a surface damp proof membrane and water vapour suppressant.	J30 (Liquid applied damp proofing) 10, 130, M12, 10, 110
Trisol 23	Concentrated, low-odour sterilisation fluid for the treatment of dry rot in masonry.	C52 (Fungus/beetle eradication) 62, 343
Tritec	Water soluble, insecticidal wood preservative.	C52 (Fungus/beetle eradication) 47, 323
Tritec Plus	Water soluble, insecticidal and fungicidal wood preservative.	C52 (Fungus/beetle eradication) 47, 323
Tritject Rapid	Water based dpc system designed for injection into walls affected by rising damp.	C45 (Damp proof course renewal/insertion) 30, 220
Triton Injection Mortar (TIM)	Single component injection mortar, designed to combat rising damp.	C45 (Damp proof course renewal/insertion) 30, 220
Triton Tri-gel	Rising damp treatment, based on a water soluble thixotropic gel.	C45 (Damp proof course renewal/insertion) 30, 220
Triton TT Vapour Membrane and gas barrier	A high performance elastomeric liquid rubber membrane.	J30 (Liquid applied damp proofing) 10, 130
TT Super	A surface applied material which waterproofs and protects concrete.	J10 (Cementitious mortar tanking/damp proofing) 130
TT Super Admix	Concrete waterproofing admixture.	J10 (Cementitious mortar tanking/damp proofing) 120
TT Swell Mastic	A gun applied, one component hydro reactive expansion sealant for waterproofing joints in concrete.	E40 (Designed joints in situ concrete) 530
TT Waterstop	Triton TT Waterstop is preformed and consists of sodium bentonite and butyl rubber.	E40 (Designed joints in situ concrete) 310
TT55 Waterproof Slurry	A single component, polymer modified cement 'tanking' system.	J10 (Cementitious mortar tanking/damp proofing) 110