

Triton Chemical Manufacturing Co. Ltd
129 Felixstowe Road, Abbeywood, London SE2 9SG
Telephone: 020 8310 3929
Fax: 020 8312 0349



MSDS Ref:
TR

Publication date
01/09/2006

Revision date

1. PRODUCT NAME: TRI-CREAM (Advanced D.P.C Injection System)

2. COMPOSITION

Hazardous ingredient	CAS No.	EC No.	Weight %	Symbols	Risk Phrases
White Mineral Oil	92062-35-6		50<75%	Xn	
Siloxane & Alkylalkoxysilane			15%	Xi, N	

3. HAZARD IDENTIFICATION

This product is not classified under the Chemicals Hazard Information and Packaging Regulations 2002

4. FIRST AID

CONTACT WITH SKIN	Remove contaminated clothing. Wash affected skin with soap and plenty of water.
CONTACT WITH EYES	Wash copiously with water or eye wash for at least 15 minutes. If symptoms persist seek medical attention.
INGESTION	Rinse out mouth and then drink plenty of water. Consult doctor as soon as possible. Keep the person affected quiet.
INHALATION	Remove to fresh air.

OTHER INFORMATION

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA	Water mist, alcohol foam, carbon dioxide or dry chemical.
SPECIFIC HAZARDS	None
CLEAN-UP PROCEDURES	Collect contaminated fire fighting water separately. It must not enter drains. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6. HANDLING AND STORAGE

HANDLING PRECAUTIONS Wear rubber gloves and safety glasses or goggles.

STORAGE INFORMATION Keep containers sealed and store above 5°C

7. EXPOSURE CONTROLS/PERSONAL PROTECTION



Wear goggles or face shield, PVC or synthetic rubber gloves, protective footwear, and overalls.
It is advisable to wear a suitable head covering and to apply a barrier cream (water-resistant type).
Use only in well ventilated areas.
Respiratory protection: Not normally required.

8. SPILL OR LEAK PROCEDURES

Do not allow to enter drains or sewers. Contain and absorb onto earth or sand and sweep up. Dispose of in accordance with local regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White Cream	Odour	None
PH	-	Boiling Point	-
Melting Point	-	Flash Point	> 100° C
Self-inflammability	Product is not self igniting	Autoignition Temp.	-
Oxidising Properties	-	Solubility in Water	Fully Miscible
Relative Density @ 20°C	0.86 g/cm ³	Vapour Pressure	-

10. STABILITY/REACTIVITY

CONDITIONS TO AVOID Avoid working in confined spaces with poor ventilation.

MATERIALS TO AVOID Avoid any strong acids and strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: None if used properly.
None if stored properly.
In the long term ethanol is formed by hydrolysis.

11. TOXICOLOGICAL INFORMATION

INHALATION Alkoxy silane: Do not inhale aerosol mist because of the risk of lung damage.

SKIN CONTACT No irritating effect.

SKIN ABSORPTION - (Cont'd)

11. TOXICOLOGICAL INFORMATION (cont'd)

EYE CONTACT	No irritating effect.
INGESTION	No acute oral data available
ACUTE OVEREXPOSURE	-
CHRONIC OVEREXPOSURE	-

12. ECOLOGICAL INFORMATION

BIODEGRADABILITY	Product hydrolyses to ethanol, silanol and/or siloxanol compounds.
AQUATIC TOXICITY	Considered to be a weak water pollutant.

13. DISPOSAL CONSIDERATIONS

DISPOSAL OF PRODUCT	Disposal through an authorised contractor to an incinerator site. In accordance with the Control of Pollution Act 1974. Control of pollution (Special Waste) Regulations 1980 apply. Hazardous waste as defined by EC Council Directive 91/689/EEC. Disposal outside the UK in accordance with local regulations governing hazardous liquid and solid wastes.
---------------------	---

14. TRANSPORT INFORMATION

PACKAGING	5 litre Tub.
-----------	--------------

Not classified as hazardous for transport purposes.

15. REGULATORY INFORMATION

The COSHH Regulations 2002 may apply to the use of this product at work.

16. OTHER INFORMATION

BWPDA DP6: Safety in damp proofing

The information contained in this data sheet is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.
