



# Triton TRIMETHRIN OS WOOD PRESERVATIVE

## Description and Use

Triton TRIMETHRIN OS is an organic solvent wood preservative formulated for the eradication of wood boring insect attack in timber.

A specific feature of Triton TRIMETHRIN OS is approved under the Control of Pesticides Regulations for professional and household use as directed.

## Composition

Triton TRIMETHRIN OS contains 0.2% w/w (1.6 grams per litre) of Permethrin dissolved in a low odour hydrocarbon solvent boiling between 195 and 260°C. The calculated LD50 value of Triton TRIMETHRIN OS is greater than 10,000 mg/kg. This represents a much safer level of toxicity compared with Lindane or Dieldrin based preservatives.

## Physical Properties

Appearance	Clear pale straw coloured liquid
Odour	Mild odour of kerosene
Specific gravity	0.80
Flash point	68-70°C (154-158°F)
Solvent	Hydrocarbon, containing less than 2% aromatic hydrocarbons

## Application

- Before treatment, heavily infested wood, frass and loose dust must be removed from all timber surfaces to be treated. Where timber is affected by wood rotting fungi use one of the Triton plus preservatives.
- Before treatment turn off electricity, remove hot surfaces and extinguish naked flames.
- Apply the preservative using a low-pressure coarse jet spray to refusal and at a rate of 1 litre per 4 square metres of wood surface area.
- During treatment the operator should wear protective clothing (gloves, apron, eye protection and mask).
- Avoid spraying on to rubber cable, foamed plastic, polystyrene and bitumastic material.
- After treatment leave the area well ventilated and leave a notice on site showing that the area has been treated and that no naked flames should be used in the areas.
- Areas inhabited by bats should not be treated until the Nature Conservancy Council have been notified.
- Triton TRIMETHRIN OS is safe for use in bat inhabited areas.

## Specification

NBS Clause C52 47, 323 Fungus / beetle eradication

HSE No. 4621

## Storage

- Store in the original container in a safe place.



## Packaging

---

Triton TRIMETHRIN 02 is supplied in 5 litre, 25 litre and 200 litre containers.

## Health & Safety

- HSE No. 4621 - 48hr re-entry
- For full information consult the relevant Material Safety Data Sheet.

\* for chemical resistances please contact your Triton representative.

For further information please contact:

**Triton Chemical Manufacturing Co Ltd T/a Triton Systems**

Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

**Tel:** 01322 318830

**Fax:** 01322 524017

**Email:** [info@tritonsystems.co.uk](mailto:info@tritonsystems.co.uk)

[www.tritonsystems.co.uk](http://www.tritonsystems.co.uk)

Ref: Triton Trimethrin OS 07/11