



ANTIMOULD EMULSION

AQUEOUS EMULSION FUNGICIDAL COATING (MOULD INHIBITING)

DESCRIPTION An excellent, premium quality low odour antimould coating guaranteed to protect against unsightly and unhygienic black mould even when there is persistent condensation. The antimould biocide is combined throughout the paint film, which is formulated to impart toughness, elasticity, water resistance and durability to the finish.

PREPARATION

- 1) Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper. **Surface Cleanser** can be used for “wetting in” purposes when removing wallpaper.
- 2) Make good any defects in the surface and rub down to a smooth finish.
- 3) Wash and clean all surfaces (walls, ceilings, window frames and joinery) using **Surface Cleanser**. If necessary clean badly affected areas a second time.
- 4) Allow to dry thoroughly.
- 5) If necessary, apply an appropriate primer or sealer to new, unprimed or porous plaster and wooden surfaces or bare metal.
- 6) For new or porous surfaces use **Antimould Emulsion** thinned up to 10% with clean tap water. Allow to dry thoroughly. After priming, metal surfaces should be painted with two coats Acrylic Gloss.

APPLICATION

- 1) Apply **Antimould Emulsion** using a brush or roller.
- 2) STIR THOROUGHLY BEFORE USE.
- 3) Apply two coats of **Antimould Emulsion** allowing sufficient drying time between coats.
- 4) Clean equipment with clean tap water before the paint dries.

N.B. If an unfinished, textured wallpaper (blown vinyl, woodchip) or similar is to be used then it should be hung after the **Surface Cleanser** has fully dried. The wallpaper should be coated with **Antimould Emulsion** as above.

TECHNICAL SPECIFICATION

Coverage: 10-12m² per litre but an extra allowance should be made for rough or porous surfaces.
Drying Time: Touch dry 1 hour and recoatable after 2-4 hours dependent on conditions.
Thinning: Use clean tap water but do not exceed 10% by volume.
Uses: Can be used as a primer and undercoat for Acrylic Eggshell or Acrylic Gloss.
Colours: Brilliant White, Magnolia and selected pastel colours. Specific colours may be supplied depending upon requirements.
Packaging: 2.5 and 5.0 litres in HPDE containers.
Storage: Store above 5°C in dry conditions. Keep the container tightly sealed and away from children.
Shelf Life: Correctly stored, the unopened product has a shelf life of 12 months.

HEALTH AND SAFETY

The product is approved under the Control of Pesticides Regulations 1986 for use as directed (HSE No. 6308). In use the product is very similar to conventional high quality emulsion paint: refer to Material Safety Data Sheet before using the product.

The information given in this data sheet is given in good faith and is based upon knowledge and experience of the materials used. However, since the application of the product is beyond the control of Triton Chemical Manufacturing Company. The Company cannot accept the responsibility for any loss or damage resulting from the use of the product outside the scope of the intended use and precautions set out in the data sheet.

For further information contact:

Triton Chemical Manufacturing Co Ltd

Unit 5, Lydean Industrial Estate

129 Felixstowe Rd, Abbey Wood, London, SE2 9SG

Telephone: 020-8310-3929 Fax: 020-8312-0349

www.triton-chemicals.com

info@triton-chemicals.com

Ref:10/00 DATA.ANTIMOULD EMULSION